

FE5MP-WDRDN-360

5MP Professional Indoor Fisheye Dome Network Camera



Features:

- 5MP Resolution 12.5/15fps
- Fixed 1.05mm Lens
- True Day & Night
- D-WDR(ATR-EX)
- Audio In/Out(1/1), Alarm In/Out(1/1)
- Micro SD Card up to 128GB
- PoE, 12VDC

Key Functions

- Auto Exposure, Auto White Balance
- Triple Stream(H.264, MPEG4, MJPEG)
- Onvif Prole S
- Easy Install: Zero Conguration, Discovery, PoE
- Event Boosting, FTP Image Upload, Web Casting, Open VPN, QoS, IP Filtering
- Cross Web Browsing(IE, Safari, Firefox, Chrome)
- Privacy Masking
- AIHM Event
- Event Buffering

Distributed by:

Technical Specs:

FE5MP-WDRDN-360

IMAGE	
Lens	Fixed 1.05mm, F2.8
Angle of View	180°(H)x180°(V)
Image Sensor: Type	1/1.8" SONY STARVIS CMOS Sensor
Image Sensor: Pixels	3096(H)x2080(V)
Min. Illumination	Color: 0.3Lux@F2.8 / BW: 0.07Lux@F2.8
Scanning Mode	Progressive Scan
Wide Dynamic Range	D-WDR(72dB)
Day and Night Mode	True D/N(Auto, Day, Night)
Noise Reduction	3DNR
Digital Zoom	16X
Exposure Control	Auto
White Balance Control	Auto, Incandescent, Fluorescent, Outdoor
Back Light Compensation	Yes
Image Eect	Flip, Mirror, Defog, HLC
Flicker Free Mode	50Hz, 60Hz
Shutter Speed	Auto (1/10,000~1sec), Manual
VIDEO/AUDIO	
Compression	H.264 (Baseline, Main, High Prole), MJPEG
Bitrate Control	CVBR, VBR
Resolution	2592x1944, 2048x1536, 1944x1944, 1440x1440, 1280x1024, 1280x960, 1024x1024, 1024x768, 720x720, 704x576, 640x480, 480x480
Frame Rate	Max. 12.5/15fps@5MP
Streaming	12.5/15fps(Triple Stream : H.264x2, MJPEGx1)
Composite Out	-
Audio Compression	G.711
Audio Streaming	2 Way
SYSTEM	
Motion Detection Area	16 Programmable Area (Include Area 8, Exclude Area 8)
Privacy Mask Zone	8 Programmable Zone
FTP Uploading	MJPEG
Event Notication	E-mail, FTP, Notication Server, XML Notication, AIHM
Audio Alert	User-Dened 3 Audio Files
Login Authority	Administrator, Operator, Guest
Event Buering FTP	Pre : 30sec, Post : 30sec
SD Record	Pre : 10sec, Post : 60sec
Manual Trigger	4 Programmable Trigger
Security	Multi User Authority, IP Filtering, HTTPS, SSL
Network Time Sync	NTP Server, Synchronized Computer, Manual
Software Reset	Restart, Reset, Factory Default
Hardware Factory Reset	Yes
Auto Recovery	Backup, Restore
Remote Upgrade	Web Browsing (IE, Chrome, Safari, Firefox), SmartManager
SD Recording Mode	Event, Continuous
NETWORK	
Protocol	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, QoS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Client Software	Web, SmartManager, Client S/W, Mobile S/W
Max. User Connection	Live: 10 Users, Playback : 3 Users
API Support	Open API, Onvif Compliance
Mobile Support	Android, iOS
EXTERNAL IN/OUT	
Video Composite Out	-
Audio	1 Input, 1 Output (Terminal Block)
Alarm	1 Input, 1 Output (Terminal Block)
Ethernet	RJ-45 (10/100Base-T)
u-SD Card	SDHC, SDXC (128GB)
RS485	-
OSD Remote Control	-
ETC	
Operating Humidity	0~90%RH (Non-Condensing)
Operating Temperature	-10~+50
Power Supply	PoE(IEEE802.3af Compliance, Class0), 12VDC
Power Consumption	110mA(5.3W)@PoE / 400mA(4.8W)@12VDC
Dimension	119(Ø)x63.8(H)mm
Net Weight	Approx. 270g
Ingress Protection	-

Tel: 760-929-9596

Email: Sales@BlueWaveSecurity.com
BlueWaveSecurity.com