

Vandal Resistant Keypad Only Series

The Vandal Resistant Keypad Only Series is a family of Keypad only readers that offer an IP68 dustproof/weatherproof rating for harsh outdoor conditions and a vandal proof design. They utilize a patented Piezo ceramic switch keypad technology and one-piece construction with no moving parts to create the highest level of durability and reliability. The vandal resistant Keypad Only series readers are available as 8- or 26-bit outputs and sized to fit directly on door mullions or frames (MM) or a single gang box (SG).

Distributed by:

Vandal Resistant Keypad Only Series KP08-MM-VR, KP26-MM-VR, KP08-SG-VR, KP26-SG-VR

Features:

- LED Indicator Light and Beeper
- PoE Capable
- IP68 Rated One Piece Housing Designed for Harsh Outdoor Conditions
- Vandal Proof Mounting
- Touch Activated keypad, Operable with Gloves, Tools, etc.
- Non-Removable Anodized Keypad Graphics Will Never Wear off
- Available in 8- and 26-bit Wiegand Outputs
- Compatible with Any Wiegand Protocol Access Control System
- Easy Installation
- Recognizes Card Formats up to 85 Bits





Specifications:	KP08-MM-VR KP26-MM-VR	KP08-SG-VR KP26-SG-VR
Power Consumption	150mA (maximum)	130mA (maximum)
Operating Temperature	-40° F - 257° F	-4° F - 140° F
Transmit Frequency	125 kHz	125 kHz
Standard Keypad Output	KP08-MM-VR: 8-bit Wiegand KP26-MM-VR: 26-bit Wiegand	KP08-SG-VR: 8-bit Wiegand KP26-SG-VR: 26-bit Wiegand
Dimensions	7.19" x 1.75" x .47" (L x H x D)	4.75" x 2.95" x 1" (L x H x D)
Wire Recommendation	22/8 Shielded Cable, Non-Plenum (up to 340 feet)	22/8 Shielded Cable, Non-Plenum (up to 340 feet)

The vandal resistant Keypad Only series is ordered with the following components for the most common door configuration:

- Controller (Part# NG1-E-DK-PS)
- Door Strike (Part# ES-C478)
- BlueView Software (Part# BVSTRD, BVPRO or BVENT)
- Credential Cards/FOBs (Part# 26B-CLMS-20 or 26B-FOB-10)