

Mullion Mount Series

**PRX-MM, PRX-KP26-MM, KP08-MM
and KP26-MM**

Mullion Mount Series

The mullion mount series is a family of Prox only, Keypad only and Dual Prox/Keypad combo readers sized to fit directly on door mullions or frames. The one piece housing is fully potted and does not have any moving parts or buttons for increased durability. The mullion mount series has a blue LED backlight and border that is always illuminated when powered. When a valid credential or PIN is presented, the backlight and border will change to a green LED and a beeper will sound. If an invalid credential or PIN is received the backlight and border will change to a red LED and a beeper will sound. After the designated time the mullion mount reader will automatically return back to the blue LED backlight and border. The LED and beeper configurations can be managed and customized through our BlueView software.



Features:

- Multi-Color LED Backlight and Beeper
- Sized to Mount Directly on Door Mullions or Frames
- PoE Capable
- IP65 Rated One Piece Housing Designed for Indoor/Outdoor Use
- Available in 8- and 26-bit Wiegand Outputs, Keypad Only Models
- Compatible with Any Wiegand Protocol Access Control System
- Easy Installation
- Recognizes Card Formats up to 85 Bits

Specifications:

	PRX-MM	PRX-KP26-MM	KP08-MM and KP26-MM
Typical Read Range	2" – 4"	2" – 4"	2" – 4"
Response Time	0.2 Seconds	0.2 Seconds	0.2 Seconds
Power Consumption	130mA (maximum)	130mA (maximum)	130mA (maximum)
Operating Temperature	-4° F - 140° F	-4° F - 140° F	-4° F - 140° F
Operating Humidity	10-95% RH (non-condensing)	10-95% RH (non-condensing)	10-95% RH (non-condensing)
Transmit Frequency	125 kHz	125 kHz	125 kHz
Standard Keypad Output	n/a	26-bit Wiegand	KP08-MM: 8-bit Wiegand KP26-MM: 26-bit Wiegand
Weight	6.40 oz.	6.40 oz.	6.40 oz.
Dimensions	6" x 2.88" x 1" (L x H x D)	6" x 2.88" x 1" (L x H x D)	6" x 2.88" x 1" (L x H x D)
Wire Recommendation	22/8 Shielded Cable, Non-Plenum (up to 340 feet)	22/8 Shielded Cable, Non-Plenum (up to 340 feet)	22/8 Shielded Cable, Non-Plenum (up to 340 feet)

The Mullion Mount Reader series is ordered with the following components for the most common door configuration:

- Controller (Part# NG1-E-DK-PS)
- Door Strike (Part# ES-C478)
- BlueView Software (Part# BVSTRD, BVPRO or BVENT)
- Credential Cards/FOBs (Part# 26B-CLMS-20 or 26B-FOB-10)

Distributed by:



Tel: 760-929-9596
Email: Sales@BlueWaveSecurity.com
BlueWaveSecurity.com

CONTROLLER

SOFTWARE

CREDENTIAL
READER

LOCKING
DEVICE

REX SENSOR

ACCESSORIES

POWER